



Proppa Industries Manufacturing

ACRYLIC

(Proppa Paints Ultra)

Description	ACRYLIC ULTRA is a high opacity semi-gloss acrylic emulsion paint is specially formulated for contract work in interior and exterior wall or ceiling surfaces. It is ideally suited for use on new plaster, allowing the surface to breathe and dry out properly, whilst providing excellent obliteration at special price.
Pack Size	4L / 10L
Color Range	Color chart
Properties	Water borne paint based on a pure acrylic resin
Drying Time	Surface dry: 1-2 hrs./coat Recoating: 2-3 hrs./coat under normal conditions
Coverage	Up to 16 m ² per liter
Application	Brush , Roller or Spray gun
Thinning	Thin with clean water 20-30%
Shelf Life	18 months from the date of manufacturing (unopened). Normal storage avoids frost & excessive heat
Preparation	After suitable preparation, new or bare areas should be primed using one coat of PROPPA SEALER. Do not apply in cold or damp conditions. Ideally any dirt should be removed by lightly rubbing down with Fine Glass paper without using any water at all. Water used in any quantity tends to soak through a porous film in poor condition and may affect its adhesion particularly when heavily coated the need for a primer is dependent upon the quality and porosity of the surface. Generally speaking, if the surface is to be repainted with emulsion, direct application may normally be carried out without a primer but thinning the first coat down to enable practical application and affect a seal

Safety, Health & Environment Information

- Keep container tightly closed
- Keep out of reach of children
- In case of contact with eyes, rinse immediately with water and seek medical assistance
- Protect the product from extreme temperatures. To remove splashes of paint from skin, use soap.